



### Installation:

#### Make sure pump is turned OFF.

1. Using scissors, cut open shrinkwrapped Filtraballs package. Do not cut through Filtraballs.
2. Remove the multiport cover from the filter tank.
3. **For tanks previously filled with another medium:** Empty the tank (follow filter tank instructions). Remove, clean, and inspect the standpipe and laterals for damage. Put the standpipe and laterals back into the tank and center in the opening.
4. Cover the opening of the standpipe with duct tape to prevent balls from falling into the pipe.
5. Add the Filtraballs. Each bag (700g / 1.5 lbs) is equivalent to one sandbag (22,5kg / 50 lbs). Once filled, the Filtraballs should occupy approximately 2/3 of the tank.
6. Remove duct tape from standpipe. Reinstall the multiport cover on the filter tank.
7. Turn the pump ON in "filtration" mode and prime the pump.

### Caution:

- **DO NOT USE CLARIFIER, PHOSPHATE REMOVER, FLOCCULANT, ALUM OR ANY OTHER PRODUCT THAT MAY DAMAGE THE FILTRABALLS.** The use of these products could damage your filter and void any warranty.
- Do not add chemicals directly into the skimmer. Always dissolve and mix chemicals in water before adding them to the pool.
- **NO NEED TO BACKWASH UNLESS TANK'S PRESSURE GAUGE REACHES 25 PSI.**
- If your filter is older than 5 years. It is strongly recommended to replace the standpipe and laterals.
- Advise the water analysis center that your filter is equipped with Filtraballs when having water tests done.

### Maintenance:

#### Opening the pool:

- In the spring or when a large amount of debris is at the bottom of the pool, vacuum on "Drain" setting to avoid unnecessary filtering by the Filtraballs.

#### To clean the Filtraballs:

- A. Remove the Filtraballs from the tank.
- B. Place the Filtraballs in a suitably sized container.
- C. Add the water and cartridge cleaning solution (follow the instructions on the bottle regarding the amount required and duration of soaking).
- D. Blot the balls to remove excess water and let them dry in the sun.

#### Closing the pool:

- Remove the plug at the bottom of the tank and let the tank drain. **DO NOT REPLACE THE CAP.**
- Filtraballs can remain in the tank during the winter.

**FAILURE TO FOLLOW THESE INSTRUCTIONS MAY REDUCE THE FILTRATION CAPACITY OF THE FILTRABALLS AND COULD DAMAGE THE INTERIOR OF YOUR FILTRATION SYSTEM AND VOID ANY WARRANTY.**

*If you have a Jacuzzi brand Lazer 250 filter, make sure the filter head assembly is properly fitted. If in doubt, call a professional service technician.*

If you have any questions about this product or problems with the installation please contact:  
**[larryd@champlainplastics.net](mailto:larryd@champlainplastics.net)**