



## OPERATIONAL INSTRUCTIONS

# Pool Wake-Up!<sup>™</sup> for Spring Openings OR Pool Hibernation<sup>™</sup> for Fall Closings

### 1. READY:

Start by removing contaminants to keep water crystal clear.



FROG Leap<sup>™</sup>  
Depth Charge<sup>™</sup>

### 2. SET:

Then set your initial chlorine level.



FROG Leap<sup>™</sup>  
Reveille<sup>™</sup>

### 3. GO:

Then prevent algae with a 90-day algae protection guarantee.



FROG Leap<sup>™</sup>  
ALL-OUT<sup>™</sup>

## 1. FROG Leap<sup>™</sup> Depth Charge<sup>™</sup>



**Spring:** After balancing the pool water and inserting a new FROG Leap Anti-Bac Mineral Pac into the FROG Leap or POOL FROG System insert FROG Leap Depth Charge using steps 1 through 8.


Water Balance Guidelines	
pH:	7.2 - 7.8
Total Alkalinity:	60 - 120 ppm
Calcium Hardness:	150 - 400
Total Dissolved Solids:	<1500
Stabilizer:	20 - 80 ppm
Free Chlorine:	0.5 - 1.0 ppm

**Winter:** Before lowering the water level and discarding the used FROG Leap Anti-Bac Mineral Pac insert FROG Leap Depth Charge using steps 1 through 8.



1. With the circulation system off, set control dial to the lowest setting and remove the cap to the FROG Leap or POOL FROG System.

COLORED CAPS



2. Remove caps from FROG Leap Depth Charge with a pliers or other suitable tool.



3. Turn FROG Leap Depth Charge over so open ends face down and insert into the center of the FROG Leap Anti-Bac Mineral Pac. The ends of the pac will align with an L-shaped key in the system. DO NOT FORCE.



4. Replace cap on FROG Leap or POOL FROG System and set dial to **Setting 5**.



5. Turn on pump and allow 1 hour for the product to slowly dispense into the pool. If after 1 hour, the pac still contains some ingredient, re-insert, replace cap and run the circulation for an additional 30 minutes.



6. Remove the empty FROG Leap Depth Charge and discard or recycle.

All components are recyclable when finished dispensing.



7. Replace cap on FROG Leap or POOL FROG System and allow circulation to run at least 15 minutes before inserting any other FROG Leap products.

8. Repeat steps 1-7 if additional FROG Leap Depth Charge is required.

## 2. FROG Leap<sup>™</sup> Reveille<sup>™</sup>



Dispense FROG Leap Reveille to establish a chlorine level in the pool following the same steps 1 through 8 for FROG Leap Depth Charge.

## 3. FROG Leap<sup>™</sup> ALL-OUT<sup>™</sup>

After FROG Leap Depth Charge and FROG Leap Reveille have dispensed, test the water before adding FROG Leap ALL-OUT for a 90-day algae protection guarantee. (See [www.kingtechnology.com](http://www.kingtechnology.com) for guarantee details.) When the pH is between 7.2 - 7.8 and the chlorine level is no more than 4.0 ppm, follow steps 1-8 below:



1. Turn off pump and turn dial to the lowest setting and remove cap from the FROG Leap or POOL FROG System.

2. Remove cap from FROG Leap ALL-OUT without removing seal.



3. Insert upside down into center of FROG Leap Anti-Bac Mineral Pac pushing down firmly on key to puncture seal.



4. Replace cap by hand only. DO NOT OVER TIGHTEN. Turn control dial to **Setting 5**.



5. Turn pump on for 90 minutes allowing FROG Leap ALL-OUT to circulate through pool.



6. To remove FROG Leap ALL-OUT, turn pump off, turn dial to lowest setting, remove system cap.



7. Lift FROG Leap ALL-OUT up and allow any water in the container to drain through the system before recycling or discarding in trash.

**NOTE:** If water shows more than a hint of blue inside FROG Leap or POOL FROG System, replace the cap, turn dial to **Setting 5** and run the pump for one minute.



8. If pool size requires additional FROG Leap ALL-OUT, repeat steps 1-7.

**NOTE:** Avoid adding other chemicals until this product has been circulated (filtered) for at least 24 hours.